## Technical specification for TAB traction 2V cells type

# 2V 2PZB150



**Technical data**

| | |
|---|---|
| Nominal voltage of cells: | 2,0 V |
| Capacity $C_5$: | 150 Ah |
| Discharge current: | $C_5$/5h = 30,0 A |
| Final discharge voltage/cell | 1,70 V/cell |
| Nominal S.G. of electrolyte: | 1,29 ± 0,01 kg/l |
| Rated temperature: | 30°C |
| Specified torque for poll screws: | 20-25 Nm |
| Ventilation requirement | EN IEC 62485-3 |

**Dimensions and weight of the cell** (EN IEC 60254-2)

| | |
|---|---|
| Width (a) | 45 mm |
| Length (b) | 157,5 mm |
| Height h1 | 513 mm |
| Height h2 | 537 mm |
| Wet weight | 10,0 kg ±5% |
| Dry weight | 7,5 kg ±5% |

**Design:**

| | |
|---|---|
| Positive electrode | Tubular type with non-woven polyester gauntlet and solid grids |
| Negative electrode | Pasted grid plate with long life expander material in LA-lead alloy |
| Separation | Polyethylene (PE) micro porous separator |
| Electrolyte | Sulphuric acid with a density of 1,29 kg/l |
| Container | Polypropylene (PP) box and lid |
| Pole | Welded type or bolt-on with M10 brass insert |

**Execution of cells and batteries**

| | |
|---|---|
| Dry charge (DC) version | A battery/cell must be filled up with electrolyte and supplementary charged before use. The plates are already formed and with special process protected against oxidation. |
| Flooded - Electrolyte-charged version | A battery /cell can be installed immediately, it is already filled up with electrolyte and electrically charged. |

**TAB Tovarna akumulatorskih baterij d.d.,** Polena 6, SI - 2392 Mežica, Slovenija **Phone:** +386 2 87 02 300 **Email:** info@tab.si

## Recommended optional systems

Central water filling system - Aquamatic
Electrolyte mixing system - Airmatic
Capacitive battery electrolyte level sensor
Battery monitoring system - BMS

## Discharge characteristics

| | |
|---|---|
| EN IEC 60254-1 cycles | 1500 |
| Depth of discharge (DOD) | up to 80%* |

* Deep discharges more than 80% DOD or discharges beyond final discharge voltages (dependent on discharge current) should be avoided.




Discharging time

**Cells manufactured to existing ISO 9001, ISO 14001 and EN/IEC 60254 standards.**